



ESRTP5RFWIFIP

5 Series WiFi Wireless Programmable Room Thermostat

- Part of the 5 Series range with user interchangeable click on/off backplate
- Control at home or from your mobile phone/tablet
- Delayed Start and TPI technology
- 7 day, 5/2 day or 24 hour programming options
- Factory set programmes
- Up to six-hour boost facility
- Automatic BST/GMT 1 hour time change
- Holiday mode
- Easy to use, quick to install and compatible with our Centro App and the WiFi Smart Power Plug



5 Series WiFi Wireless Programmable Room Thermostat

The ES RTP5WIFIP is our top of the range WiFi Programmable Room Thermostat providing seamless control at home or from your mobile phone or tablet using the ESi Centro APP. It is designed for time and temperature control of your heating and comes with 7 day, 5/2 or 24 hour programming options all in one unit with a factory-set programme which can be user modified.

The simple click on/off backplate is designed to be fully interchangeable throughout the entire 5 and 6 Series range and, with just a 5 volt connection, can be upgraded to different versions safely by the homeowner without disconnecting the power or re-wiring. The new unit will simply click on to the existing backplate and be ready to use – it really is as simple as that. This gives the homeowner full control and flexibility to interchange between any of the 5 and 6 Series Room Thermostats with no need for an electrician.

Users can choose between TPI and Delayed Start energy saving features and select a landlord service interval for additional peace of mind. The ES RTP5RF uses 868Mhz 2 way technology for accurate and responsive communication and an easy retrofit solution.

ErP Class IV Product (2%)

Technical Data

5 Series Wi-fi & RF Programmable Room Thermostat	ES RTP5RFWIFIP
Temperature Control Class	ErP Class IV Product (2%)
Energy Efficiency Technology	TPI (Chrono-Proportional) Control, Delayed Start, Optimum Start, Optimum Stop
Programming	7 Day, 5/2 & 24 Hour
Operation Modes	Auto/Manual/Off (Frost Prevention)
Power Supply	230V AC
Temperature Adjustment Range	5c – 35c
Sensing Element	Electronic
Switch Rating	6(2)A 230V AC
Contact Type Tx	Wireless (RF & Wi-Fi)
RF Transmission Distance	Approx. 30m in open terrain
Wi-Fi Signal	2.4 Ghz
Plastics	Thermoplastic, flame retardant
Protection Rating	IP30
Dimensions	95mm x 95mm x 39mm
Number Of Events Per Day	4 or 6 Selectable
Clock	12 or 24 Hour Selectable
BST/GMT Time Change	Automatic
Factory Pre-set Programme	Yes
Complies with	EN60730-1 EN60730-2.7, EMC Directive 2014/30/EU, LVD Directive 2014/35/EU, Directive 2014/53/EU